



MAB 4100 grau/grey	MAB 5100 grau/grey	MAB 5100 S grau/grey	MAB 5100 S schwarz/black
930 951-517	930 952-517	930 953-517	930 953-500
female	female	female	female
grey	grey	grey	black
panel-mounted socket with locking screw; solder joint; not shielded	panel-mounted socket with locking screw; solder joint; not shielded	panel-mounted socket with locking screw; solder joint; not shielded	panel-mounted socket with locking screw; solder joint; not shielded
4	5	5	5
$\leq 0,34 \text{ mm}^2$	$\leq 0,34 \text{ mm}^2$	$\leq 0,34 \text{ mm}^2$	$\leq 0,34 \text{ mm}^2$
EN 60 130-09	EN 60 130-09	EN 60 130-09	EN 60 130-09
$\leq 4 \text{ A}$	$\leq 4 \text{ A}$	DIN 41 524	DIN 41 524
UC 34 V	UC 34 V	UC 34 V	UC 34 V
solder	solder	solder	solder
brass	brass	brass	brass
tin plated	tin plated	tin plated	tin plated
PA 66/UL standard 94V-2	PA 66/UL standard 94V-2	PA 66/UL standard 94V-2	PA 66/UL standard 94V-2
PE	PE	PE	PE
IP 30	IP 30	IP 30	IP 30
-20 °C to +60 °C	-20 °C to +60 °C	-20 °C to +60 °C	-20 °C to +60 °C